

0641, 0644, 0645 Series Pre-Mixed Concrete Patch:

- **What is the base chemistry of this formulation?** Acrylic latex base emulsion.
- **Is this formula VOC Compliant?** Yes.
- **Are any Prop 65 Ingredients in this product?** Yes – see MSDS.
- **Does this formula allow water clean up?** Yes, prior to cure.
- **Is this product paintable?** Yes.
- **Is this formula designed to be shrink & crack resistant?** Yes – when used as directed.
- **Describe the hardness of the fully cured repair?** Very hard @ full cure. (0645 squeeze tube material slightly less hard @ full cure, as compared to tub material)
- **What is the product color @ cure?** Dries to blend w/ concrete.
- **Is product suitable for vehicular traffic areas?** Not recommended.
- **Is product considered flammable?** No – flashpoint > 200F.
- **Is product Freeze/Thaw stable?** Yes – for 5 cycles.
- **What is the expected shelf-life of this product?** Expect 1 yr @ 72F, in original container.
- **What is the typical drying time of the product?** Minimum 24 hrs (depending on climatic conditions & depth of repair)
- **What is the suggested Application Temperature Range?** 40F to 90F.
- **What is the Service Temperature Range?** 0 to 200F.
- **Describe crack size limitations?** Cracks greater than a ¼ in deep, may require two or more applications.
- **Where can I learn more about this product?** See MSDS & TDS on this website (www.reddevil.com)