

Safety Data Sheet

Issue Date 19-Aug-2013 Revision Date: 01-Oct-2017 Version 1

1. IDENTIFICATION

Product Identifier

Product Name Pre-mixed Stucco Wall Patch – Acrylic – Textured - Tub

Other means of identification

SDS # RD-0050A

Product Code 0450 Series

Recommended use of the chemical and restrictions on use

Recommended Use A pre-mixed stucco patch for the repair of small holes in stucco surfaces.

Details of the supplier of the safety data sheet

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

Emergency Telephone Number

Company Phone Number 918-825-5744

Fax: 918-825-5761

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

AppearanceWhite/Off-whitePhysical StateTextured pasteOdorMild acrylic

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Crystalline silica	14808-60-7	<50
Acrylic Emulsion	MIXTURE	<25
Calcium Carbonate	1317-65-3	<20
Titanium dioxide	13463-67-7	<2
Non-hazardous Ingredients*	Proprietary	<5
Propylene Glycol	57-55-6	<2

^{*} Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Calcium Carbonate, Titanium Dioxide, and Silica) Inhalation of particulates unlikely due to product's physical state.

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Revision Date: 01-Oct-2017

Skin Contact Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist.

Remove & wash contaminated clothing.

Inhalation Remove to fresh air. If breathing is difficult, leave area to obtain fresh air. If breathing

remains difficult, get medical attention.

Ingestion Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean

patient forward to maintain an open airway & prevent aspiration. Get immediate medical

attention.

Most important symptoms and effects

Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact **Symptoms**

with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and

sneezing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Provide general supportive measures and treat symptomatically.

Medical Conditions Aggravated By Exposure: Dermatitis or other pre-existing skin

conditions may be aggravated by overexposure to this product.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Revision Date: 01-Oct-2017 Tub

Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

Hazardous Combustion Products Carbon oxides.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Other Information Small Spills: 1 drum or less - Level D Equipment (gloves, chemical resistant apron, boots &

eve protection).

Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

For Emergency Responders Restrict access to spill area.

Environmental Precautions Minimize use of water to prevent environmental contamination. Prevent spill or rinse from

contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing

this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES)

permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA

Regional Office

Other: U.S. regulations may require reporting of spills of this material reaching surface

waters if sheen is formed.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Clean-Up Sweep up absorbed material and shovel into suitable containers for disposal. Wash area

with soap and water. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use Advice on Safe Handling

> only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing. Do not eat or drink while handling this material. In event of spill – see Section 6.

Conditions for safe storage, including any incompatibilities

Storage Conditions Stable under normal conditions of handling, use & storage. Store containers in a cool, dry

location, away from direct sunlight & high temperatures. Protect from freezing. Store away from incompatible materials. Close container after each use & keep tightly closed when not

in use. To maximize shelf life, store @ temperatures below 26C (80F).

Revision Date: 01-Oct-2017

Incompatible Materials Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Crystalline silica	TWA: 0.025 mg/m ³ respirable	(vacated) TWA: 0.1 mg/m ³	IDLH: 50 mg/m³ respirable dust
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m ³ respirable
		: (30)/(%SiO2 + 2) mg/m ³ TWA	dust
		total dust	
		: (250)/(%SiO2 + 5) mppcf	
		TWA respirable fraction	
		: (10)/(%SiO2 + 2) mg/m ³ TWA	
		respirable fraction	
Calcium Carbonate	-	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust
1317-65-3		TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ respirable dust
		fraction	
		(vacated) TWA: 15 mg/m ³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m ³ total	
		dust	

Appropriate engineering controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment

Use approved safety goggles or safety glasses. If necessary, refer to appropriate **Eye/Face Protection**

regulations & standards.

Skin and Body Protection Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill

response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment)or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations &

standards.

If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below **Respiratory Protection**

19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand

SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Textured paste

Appearance White/Off-white Odor Mild acrylic Color White/Off-white **Odor Threshold** Not determined

Note: The information below is not Remarks • Method **Property**

> intended for use in preparing product specifications

RD-0050A - Pre-mixed Stucco Wall Patch - Acrylic - Textured -

Tub

Revision Date: 01-Oct-2017

рΗ 7.0-10.0

Melting Point/Freezing Point < 0 °C / <32 °F **Boiling Point/Boiling Range** Not Established

Flash Point > 93.33 °C / > 200 °F

Evaporation Rate Not determined Flammability (Solid, Gas) Not determined **Upper Flammability Limits** Unknown **Lower Flammability Limit** Unknown **Vapor Pressure** Not established **Vapor Density** Heavier than air

Specific Gravity ~1.75-2.25 @ 25 °C (77 °F)

Water Solubility Appreciable before cure

Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition Temperature** Unknown **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

VOC Content (%) <1.5% **VOC Content** <25 g/L

10. STABILITY AND REACTIVITY

Reactivity

Cures upon contact with air.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible Materials

Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Thermal decomposition can generate irritating dust, fumes and toxic gases (carbon, titanium, and iron oxides, depending upon formulation).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eve Contact Eye contact may result in tearing, redness & pain.

Skin Contact Prolonged and frequent contact may cause redness and irritation. Repeated skin contact

may cause dermatitis.

Inhalation Overexposure to vapors during application & curing may mildly irritate respiratory tract &

result in coughing & sneezing.

Ingestion

May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Revision Date: 01-Oct-2017

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Crystalline silica 14808-60-7	= 500 mg/kg (Rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Propylene Glycol 57-55-6	= 20000 mg/kg (Rat)	= 20800 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not known to be human skin or respiratory sensitizers.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder). Trace residual Formaldehyde present in base emulsion viewed as possible cancer hazard.

Chemical Name	ACGIH	IARC	NTP	OSHA
Crystalline silica 14808-60-7	A2	Group 1	Known	X
Titanium dioxide 13463-67-7		Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program) Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target organ effects Acute: Eyes & Skin. Chronic: Skin.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	

Propylene Glycol	19000: 96 h	51600: 96 h Oncorhynchus	10000: 24 h Daphnia magna
57-55-6	Pseudokirchneriella	mykiss mg/L LC50 static 41 -	mg/L EC50 1000: 48 h
0. 00 0	subcapitata mg/L EC50	47: 96 h Oncorhynchus	Daphnia magna mg/L EC50
		mykiss mL/L LC50 static	Static
		51400: 96 h Pimephales	
		promelas mg/L LC50 static	
		710: 96 h Pimephales	
		promelas mg/L LC50	

Revision Date: 01-Oct-2017

Persistence/Degradability

Not tested for persistence & biodegradability

Bioaccumulation

Not tested for bio-accumulation potential

Mobility

Not tested for mobility in soil

Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

Ozone

Not expected to produce any ozone depletion

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Listed
DSL Listed

ub

Revision Date: 01-Oct-2017

NDSL Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Crystalline silica - 14808-60-7	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Crystalline silica 14808-60-7	X	X	Х
Calcium Carbonate 1317-65-3	X	X	Х
Titanium dioxide 13463-67-7	X	X	Х
Propylene Glycol 57-55-6	X		X

16. OTHER INFORMATION

Revision Date: 01-Oct-2017

NFPA **Health Hazards Flammability** Instability **Special Hazards** Not determined **Personal Protection** HMIS **Health Hazards Flammability Physical Hazards** Not determined

Issue Date 19-Aug-2013 **Revision Date:** 01-Oct-2017 **Revision Note** New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet